

Acova Atoll



Central heating Dual energy Electric only

Height (mm) H	Width* (mm) W	Finish	Central Heating Models			Electric Immersion rating (Watts)	Net Weights (kg)	RRP (ex VAT)	RRP (inc VAT)
			Stock	Output 60Δt Watts/BTU	Output 50Δt Watts/BTU (EN442)				
748	450	white	SL-080-045	444/1517	354/1208	300	5.4	£89	£104.58
748	500	white	SL-080-050	487/1662	388/1324	300	5.6	£93	£109.28
748	600	white	SL-080-060	572/1952	455/1552	300	6.7	£101	£118.68
1148	450	white	SL-120-045	658/2245	521/1778	300	8.1	£109	£128.08
1148	500	white	SL-120-050	719/2453	571/1948	300	8.7	£113	£132.78
1148	600	white	SL-120-060	844/2880	670/2286	600	9.8	£122	£143.35
1708	450	white	SL-170-045	954/3254	751/2562	600	11.	£150	£176.25
1708	500	white	SL-170-050	1044/3562	824/2811	600	12.2	£155	£182.13
1708	600	white	SL-170-060	1221/4166	966/3296	900	14.2	£163	£191.53
748	500	chrome	SLO-080-050	359/1225	283/966	300	5.8	£173	£203.28
748	600	chrome	SLO-080-060	420/1433	332/1133	300	6.7	£183	£215.03
1148	500	chrome	SLO-120-050	528/1802	417/1423	300	8.7	£225	£264.38
1148	600	chrome	SLO-120-060	621/2119	489/1668	300	9.8	£244	£286.70
1708	500	chrome	SLO-170-050	763/2603	601/2050	600	12.2	£327	£384.23
1708	600	chrome	SLO-170-060	895/3054	705/2405	600	14.2	£346	£406.55
746	500	stainless steel	SLI-080-050	353/1204	280/955	300	5.2	£176	£206.80
1146	300	stainless steel	SLI-120-030	333/1136	262/894	300	5.7	£192	£225.60
1146	500	stainless steel	SLI-120-050	527/1798	416/1419	300	8.1	£255	£299.63
1146	600	stainless steel	SLI-120-060	620/2115	491/1675	300	9.3	£338	£397.15
1466	300	stainless steel	SLI-150-030	417/1423	327/1116	300	7.4	£322	£378.35
1706	300	stainless steel	SLI-170-030	478/1631	374/1276	300	7.6	£333	£391.28
1706	500	stainless steel	SLI-170-050	753/2569	594/2027	600	11.2	£390	£458.25

Max. test pressure: 15 Bar / Stainless Steel: 13 Bar Max working pressure: 11.5 Bar / Stainless Steel: 10 Bar

An immersion heater for dual energy use can only be fitted in the header tube without the insert tube. (see page 101 for details)

Overall projection: 87-102mm Wall to centre of connections: 68-83mm Pipe centres: width minus 38mm

Dual energy: Dependant on installation

Valves & Accessories: Please refer to accessories section (page 103) & valves (page 102) for details and prices.

Finish: Stainless Steel - polished Colour finishes not available.

Height (mm) H	Width† (mm) W	*Finish	Electric only (With factory fitted DBM immersion)		Electric Immersion rating (Watts)	Net Weight (kg)	RRP (ex VAT)	RRP (inc VAT)
			Stock	Class II, IPX4, IK09, BEAB (Zone 1 bath, Zone 2 shower)				
1068	500	White	TSL-050-050-DF		500	11.6	£240	£282.00
1428	500	White	TSL-075-050-DF		750	15.8	£288	£338.40
1828	500	White	TSL-100-050-DF		1000	21.1	£356	£418.30
1068	500	Chrome	TSLO-030-050-DF		300	11.6	£435	£511.13
1428	500	Chrome	TSLO-050-050-DF		500	15.8	£477	£560.48
1828	500	Chrome	TSLO-075-050-DF		750	21.1	£634	£744.95

Overall projection: 68-83mm

The DBM is fitted to the right hand header as standard.

The radiator can be reversed to have the immersion heater on the left hand side, and the control panel turned to face the front.

Accessories: please refer to page 103

*Colour finish not available

